

pHastTrac® 2000

12/09



6103 GLENMONT • HOUSTON, TEXAS • 77081
800/522-7920 • FAX 713/772-4671 • 713/772-6641
www.VL-PC.com



Standard Features

- Replaceable Sensor
- Retract / Insert from Process Lines & Tanks
- Integrated Clean / Calibration and / or S.I.P. Chamber
- Reduced Direct Electrode Handling

Specifications

- **Temperature Range:**
During Operation: 2000 Series: 0 to 90°C
- **Pressure Range:**
0-100 PSI @ 25°C
0-50 PSI @ 90°C
- **Wetted Materials:**
316L Stainless Steel
Viton® O-Rings

The proven design of the **pHastTrac® 2000** is ideal for applications in the food, process, pharmaceutical and many other industries where frequent cleaning and calibration of electrodes are required. Incorporated in this system is a clean / cal chamber that allows the user to remove the electrode from a process line or tank while maintaining production integrity.

With the center pivot in the retracted position, the electrode is now ready to be cleaned and calibrated. By using the **pHastTrac® 2000** system, the electrode is never directly handled during operation, resulting in fewer electrode failures due to negligence or operator error.

Electrodes for the Van London - pHoenix Co. **pHastTrac® 2000** are available for virtually any application need. See the proce list for details on which electrode best suits your application.

pHastTrac is a Trademark of Van London-pHoenix Electrode Co.
Viton is a Trademark of E.I. du Pont de Nemours & Co

**FOR ADDITIONAL PRODUCT INFORMATION,
CALL 713/772-6641 OR 800/522-7920
E-mail: sales@VL-PC.com
www.VL-PC.com**